

Switched Mode Power Supply - DIN Mount

- Excellent Load & Line Regulation
- High Noise Immunity & Low Ripple
- No Load Power Consumption of less than 0.5W
- Overload & Short Circuit Protection
- High Efficiency of Operation
- Suitable for Temperatures upto 55°C
- Small Form Factor
- Peak Power Capacity
- Compact Design with DIN Mounting
- CE and RoHS complied



Ordering Information

Cat. No.	Description
24AS244D6D	96W, 230V AC, 24 VDC / 4A, Switched Mode Power Supply (6M Size)
24AS126D6D	72W, 230V AC, 12 VDC / 6A, Switched Mode Power Supply (6M Size)
24BS24AD4E	60W, 110 - 240 VAC, 24 VDC / 2.5A, Switched Mode Power Supply (4M Size)
24BS241D2F	24W, 110 - 240 VAC, 24 VDC / 1A, Switched Mode Power Supply (2M Size)
24BS24BD1F	12W, 110 - 240 VAC, 24 VDC / 0.5A, Switched Mode Power Supply (1M Size)
24BS121D2F	12 W, 110 - 240 VAC, 12 VDC / 1.0A, Switched Mode Power Supply (2M Size)
24BS101D2F	10 W, 110 - 240 VAC, 10 VDC / 1.0A, Switched Mode Power Supply (2M Size)
24BS051D1F	5W, 110 - 240 VAC, 5 VDC / 1.0A, Switched Mode Power Supply (1M Size)

Switched Mode Power Supply - DIN Mount / Panel Mount

- Excellent Load & Line Regulation
- High Noise Immunity & Low Ripple
- Overload, Overload, Short Circuit & Over Temperature Protection
- High Efficiency of Operation
- Suitable for Temperatures upto 70°C
- Small Form Factor
- Peak Power Capacity
- Compact Design with DIN Mounting
- CE and RoHS complied



SMPS 150W



SMPS 100W

Ordering Information

SMPS 150W

Cat. No.	Description
PS150W24V	150W, 85 - 132 VAC/170 - 264 VAC, 24 VDC/ 6.25A, Terminal Block Facing Upward, Switch Mode Power Supply
PS150W24VF	150W, 85 - 132 VAC/170 - 264 VAC, 24 VDC/ 6.25A, Terminal Block Facing Forward, Switch Mode Power Supply

Accessories	Description
L15024	Mounting Bracket for SMPS

SMPS 100W

Cat. No.	Description
PS100W24V	100W, 90 - 264 VAC/130 - 373 VDC, 24 VDC/ 4.5A, Terminal Block Facing Upward, Switch Mode Power Supply
PS100W24VF	100W, 90 - 264 VAC/130 - 373 VDC, 24 VDC/ 4.5A, Terminal Block Facing Forward, Switch Mode Power Supply

Accessories	Description
L10024	Mounting Bracket for SMPS

Slim Relays

1 change over

- Compact 6.2 mm slim design
- Variety of Operating voltages (24 VDC, 24 VAC/DC, 120 VAC/DC, 230 VAC, 230 VAC/DC)
- Output Relay: 1 C/O for high switching current up to 6A at 250VAC
- All sockets with LED for relay status
- Shorting Link, Marker & end clamp available as accessories
- CE and RoHS complied



1 change over

2 change over

- Compact 14 mm slim design
- Variety of Operating voltages (12 VAC/DC, 24 VAC/DC, 120 VAC/DC, 230 VAC/DC)
- Output Relay: 2 C/O for high switching current up to 8A at 230VAC
- All sockets with LED for relay status
- Shorting Link, Marker & end clamp available as accessories
- CE and RoHS complied



2 change over

Ordering Information

1 change over

Cat. No.	Description
SR24D61RM	Slim Relay Module with Plugin Relay 24VDC, 1 C/O DIN Mount ¹
SR24U61RM	Slim Relay Module with Plugin Relay 24VAC/DC, 1 C/O DIN Mount ¹
SR120U61RM	Slim Relay Module with Plugin Relay 120VAC/DC, 1 C/O DIN Mount ¹
SR230A61RM	Slim Relay Module with Plugin Relay 230VAC, 1 C/O DIN Mount ¹
SR230U61RM	Slim Relay Module with Plugin Relay 230VAC/DC, 1C/O DIN Mount ¹

2 change over

Cat. No.	Description
SR12U82RM	Slim Relay Module with Plugin Relay 12VAC/DC, 2 C/O DIN Mount ¹
SR24U82RM	Slim Relay Module with Plugin Relay 24VAC/DC, 2 C/O DIN Mount ¹
SR120U82RM	Slim Relay Module with Plugin Relay 120VAC/DC, 2 C/O DIN Mount ¹
SR230U82RM	Slim Relay Module with Plugin Relay 230VAC/DC, 2 C/O DIN Mount ¹

NOTE: 1 - Pack of 10nos